



AUTOMOTIVE LUBRICANTS

MOL Farm Protect 10W-40

multigrade diesel motor oil

Product benefits

- for heavy duty diesel engines
- semi-synthetic formula
- long drain interval
- high performance level
- long engine life
- can be used all through the year
- keeps the engine parts clean
- excellent viscosity and shear stability
- high level wear protection

Applications

MOL Farm Protect 10W-40 is a semi - synthetic engine oil for high performance naturally aspirated and turbocharged agricultural diesel engines, specially formulated for long drain intervals.

Especially recommended for modern in heavy duty conditions diesel engines of trucks, off-highway machinery and harvesters used in the agriculture and construction machines and industrial equipment.

The product is an ideal lubricant for all modern high load diesel engines with EGR and SCR systems.

It provides long lifetime and excellent wear protection for the engines.

Suitable for European and American heavy duty diesel engines used in the agriculture.

Specifications and approvals

Viscosity grade: SAE 10W-40

ACEA E7-08 Issue 2

ACEA A3/B4-10

ACEA A3/B3-10

API CI-4

Global DHD-1

JASO DH-1

MAN M 3275-1

Volvo VDS-3

Renault RLD-2

MTU Type 2

Cummins CES 20078

Cummins CES 20077

MACK EO-M Plus

DDC 93K215

Allison C-4

Deutz DQC III-10

Mack EO-N

Manufactured and distributed by MOL-LUB Ltd.

E-mail: lubricants@mol.hu Web: mol.hu

Technical service: H-1117 Budapest, Budafoki u 59.

H-1986 Budapest, MOL Plc. Tel: + 36 (1) 464-02-36 Fax: +36 (1) 464-03-04 Web: mol.hu/engineering/en

Latest revision: 2014.12.02 8:33

Version 028.000.



AUTOMOTIVE LUBRICANTS

MOL Farm Protect 10W-40

multigrade diesel motor oil

Product description

MOL Farm Protect 10W-40 is specially formulated for the high requirements of agricultural machines. It is produced from highly refined mineral oils and synthetic base oils with multi-purpose, well-balanced additive system (detergent/dispersant, antiwear, antioxidant, anticorrosive, antifoam and acid neutralizing agents) as well as components for the favourable flow properties.

It provides full engine protection in all service conditions, keeps internal engine parts clean, reduces the wear of engine components, prevents corrosion and neutralizes acidic compounds during operation.

Due to its thermal and oxidative stability prevents sludge and deposit formation and provides long drain oil intervals, prolongs engine life and reduces down time.

Due to its excellent evaporation characteristics it reduces oil consumption, and consequently the emission of harmful chemicals.

Its excellent rheological properties provide easy cold starting during winter period (it remains liquid down to a temperature of -33 °C) and adequate load carrying capacity of the lubrication film during summer as well.

Typical properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,870
Kinematic viscosity at 40°C [mm ² /s]	96,9
Kinematic viscosity at 100 °C [mm ² /s]	14,7
Viscosity index	158
Pour point [°C]	-38
Flash point (Cleveland) [°C]	220
Base number (BN) [mg KOH/g]	10,4

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects. The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Inflammability hazard: Grade IV.

Recommended storage temperature: max. 40°C



AUTOMOTIVE LUBRICANTS
MOL Farm Protect 10W-40
multigrade diesel motor oil

Ordering information

SAP code and packaging:

13007233 10 l plastic can
13007081 60 l steel drum
13007082 216.5 l steel drum

Order booking (toll-free):

Phone: 80/201-331 (between 07-16 h weekdays)